GENERAL PURPOSE MORTAR

FP McCann General Purpose Mortar is a factory produced mortar consisting of blended sand, Portland cement and special additives that conforms to BS EN 998-2 and meet the requirements of a designation III strength category (M4) mortar.

FEATURES

- Available in 20kg bags
- Produced in a factory controlled environment – consistent high level quality
- Quick and convenient to use, just add water
- All material required is contained with this bag. Adding additional material is not recommended

TYPICAL APPLICATION

- General repairs & maintenance
- Brick & Block Laying
- Pointing & Patching

WHERE & WHEN TO USE

- Suitable for both internal and external use
- Recommended for use between temperatures of +5˚C and +30˚C

APPLICATION GUIDANCE

- When using this product, good site practice should always apply.
- Mortar must be of a consistent stiffness prior to pointing to reduce any colour variations
- Protect newly placed mortar from weather until fully hardened
- FP McCann cannot be held responsible where workmanship has failed to meet the relevant European and British Standards.

MIXING & WATER GUIDANCE

- For best results, mix using a mechanical mixer
- Add contents of bag in mixer
- Add approximately 3 to 4 litres of water and mix continuously for 3-4 minutes until desire consistency is achieved
- Avoid over mixing as this can reduce strength and durability of the mortar

SALES & TECHNICAL SUPPORT

Should you require additional information on this product, please contact our sales team on:

Telephone 028 79642 558 or
Email sales@fpmccann.co.uk

Additional information can be obtained from fpmccann.co.uk/bagged-products/

ALL PACKAGING IS WEATHERPROOF AND RECYCLABLE

COMPRESSIVE STRENGTH

Approximately 5-10Nmm² after 28 days

STORAGE GUIDANCE

- Please ensure unopened bags are stored in cool dry conditions, preferably on a pallet or shelf to keep elevated from the ground and protected from wind and rain
- If the product is stored correctly (as detailed above), the Chromium (VI) in this product will be within required levels for up to 12 months
- Use of this product after the declared storage period can be hazardous. Prolonged storage beyond 12 months may increase the level of Chromium (VI) and may increase the risk of allergic reaction following direct contact with skin.

FOR UP TO DATE TECHNICAL ADVICE AND INFORMATION ON OUR BAGGED PRODUCT RANGE SCAN THE QR CODE